

NVR4.0 H.265 Series 16 channels

The most easy-to-use, popular and commercial 16 channel embedded NVR; specially design for store, small warehouse, office and family, access HD IPC, provide preview, recording, forward and so on functions. Support mobile phone monitoring, traversal service, achieve APP seconds connection for preview and remote recording playback, support various network modes:
 IPC----NVR---- Seetong Cloud----Seetong Client
 IPC-----NVR-----Seetong Client
 IPC----NVR---- Seetong Cloud----Seetong APP



H.265+, 4K, Stable, easy to use, perfect.

Orders	Specification	TS8216A3 2 Disk 16CH H.265+ NVR
1	System Structure	Embedded LINUX design, pure hardware decode, watchdog, hard disk storage, HDMI HD display, IP network video access. Main processor Hi3798M;
2	Video Input	HD IPC access, each channel support dual stream access, support auto search, add, recording, preview and without debugging Access bandwidth 76Mbps;
3	Video Output	1 channel HDMI output, support 4K (3840×2160)/30Hz, 1920×1080, 1440×900, 1366×768, 1280×1024, 1280×800, 1024×768 resolution output show; 1 channel VGA output, homology with HDMI, support 1920×1080, 1440×900, 1366×768, 1280×1024, 1280×800, 1024×768 resolution output show; Support Seetong client preview, APP preview and seconds connection 1/2/4/6/8/9/16 pictures real time preview;
4	Video Capacity	Support H.265+/H.265/H.264 decoding; Video recording resolution: 720P/960P/1080P/3MP/4MP/5MP/4K(8MP); NVR local recording playback support 4CH 2MP, 2CH 4MP, 1CH 4K; Seetong client recording playback support 4 channels.
5	Audio	Standard G.711, support audio and video recording, support HDMI output channel preview and playback audio and video, Seetong client audio and video preview and playback;
6	Storage	2*SATA hard disk interface, support 500GB~6TB capacity; Support schedule record, motion detection linkage record; Support external USB storage devices (such as ordinary U disk, mobile hard disk) backup;
7	User	Local maximum support for 16 users;
8	Network Interface	1*RJ45 Ethernet interface, support 10/100M self-adaption; support TCP/IP, IPv4, DHCP, NTP, RTSP, ONVIF, P2P, SMTP, GB28181 and so on protocols;
9	Peripheral Interface	2*USB2.0 interface(rear); support for the mouse, USB upgrade, import and export;
10	Front Panel	1* power, 1*record, 1*network indicator light;
11	Business Functions	Support preview/recording/forward/remote service, support alarm linkage, support Seetong client remote control software; support seetong cloud service;
12	Working	-10°C~+55°C

	Temperature	
13	Working Humidity	10%~90%
14	Others	DC +12V/4A power input, host power consumption \leq 3W (No disk), size 335*253.5*50mm (W*D*H), weight 1357g;