

NVR4.0 H.264 Series 16 channels

The most easy-to-use, popular and commercial 16 channel embedded NVR; specially design for store, small warehouse, office and family, access 16 channel 1080P HD IPC, provide preview, recording, transmit and so on functions. Support mobile phone monitoring, seetong cloud service, achieve APP seconds connection for preview and remote recording playback, support various network modes:

IPC ----- NVR ----- Seetong Cloud-----Seetong Client

IPC ----- NVR ----- Seetong Client

IPC ----- NVR ----- Seetong Cloud-----Seetong APP



Stable, easy to use, perfect.

Orders	Specification	TS9216Q3 2 Disk 16 Channel H.264 NVR
1	System Structure	Embedded LINUX design, dual core DSP, pure hardware decode, watchdog, hard disk storage, HDMI show, IP network video access. Main processor Hi3520D V200;
2	Video Input	HD IPC access, each channel support dual stream access, support auto search, add, recording, preview and without debugging 16 channels 720P/16 channels 960P/16 channels 1080P; Support H.264 ultralow code rate access;
3	Video Output	1 channel HDMI output, 1 channel VGA output, support display on the same screen Support multi pictures division; support 1920×1080, 1440×900, 1366×768, 1280×1024, 1280×800, 1024×768 resolution output show 1/2/4/6/8/9/16 pictures real time preview; support Seetong client preview, APP preview and seconds connection NVR local recording playback support 2 channels 2MP; Seetong client recording playback support 4 channels.
4	Video Capacity	2*SATA II hard disk interface, support 3.5 inch SATA II hard disk, support 500GB~8TB capacity (recommend SV35 hard disk), support recording storage, H.264 recording, local recording playback and remote control playback. Video recording: 720P/960P/1080P;
5	Network Interface	1*RJ45 Ethernet interface, support 10/100M self-adaption; support 16pcs remote client visit, support TCP/IP, DHCP, NTP, SMTP, P2P, ONVIF and so on protocols
6	Peripheral Interface	2*USB2.0 interface
7	Front Panel	1* power, 1* record, 1* network indicator light;
8	Optional Interface	1*USB2.0 composite interfaces; 1*5V power output interface; 1* buzzer interface;
9	Business Functions	Support preview/recording/forward/remote service, support alarm linkage, support Seetong client remote control software; support seetong cloud service;
10	Working Temperature	-10°C~+55°C
11	Working Humidity	10%~90%

12	Others	DC +12V/2A power input, host power consumption \leq 3W (No disk), size 335*253.5*50mm (W*D*H), weight 1367g;
----	--------	--