

NVR4.0 H.265 Series 4 channels PoE NVR

The most easy-to-use, popular and commercial 4 channel H.265+ PoE NVR; specially design for store, small warehouse, office and family, access HD IPC, provide preview, recording, forward and so on functions. Support mobile phone monitoring, traversal service, achieve APP seconds connection for preview and remote recording playback, support various network modes:
 IPC----NVR---- Seetong Cloud----Seetong Client
 IPC-----NVR-----Seetong Client
 IPC----NVR---- Seetong Cloud----Seetong APP



PoE, H.265+, 4K, Stable, easy to use, perfect.

Orders	Specification	TS6104C3 1 Disk 8CH H.265+ PoE NVR
1	System Structure	Embedded LINUX design, pure hardware decode, watchdog, hard disk storage, HDMI HD display, IP network video access.
		Main processor Hi3536C;
2	Video Input	HD IPC access, each channel support dual stream access, support auto search, add, recording, preview and without debugging
		Access bandwidth 40Mbps;
3	Video Output	1channel HDMI output, support 4K (3840×2160)/30Hz, 1920×1080, 1440×900, 1366×768, 1280×1024, 1280×800, 1024×768 resolution output show;
		1 channel VGA output, homology with HDMI, support 1920×1080, 1440×900, 1366×768, 1280×1024, 1280×800, 1024×768 resolution output show;
		Support Seetong client preview, APP preview and seconds connection
		1/2/4 pictures real time preview;
4	Video Capacity	Support H.265+/H.265/H.264 decoding;
		Video recording resolution: 720P/960P/1080P/3MP/4MP/5MP;
		NVR local recording playback support 4CH 2MP, 2CH 5MP; Seetong client recording playback support 4 channels.
5	Audio	Standard G.711, support audio and video recording, support HDMI output channel preview and playback audio and video, Seetong client audio and video preview and playback;
6	Storage	1*SATA hard disk interface, support 500GB~8TB capacity;
		Support schedule record, motion detection linkage record;
		Support external USB storage devices (such as ordinary U disk, mobile hard disk) backup;
7	User	Local maximum support for 16 users;
8	Network Interface	1*RJ45 Ethernet interface, support 10/100M self-adaption; support TCP/IP, IPv4, DHCP, NTP, RTSP, ONVIF, P2P, SMTP, GB28181 and so on protocols;
9	PoE Interface	4 PoE ports, support 802.3af and 802.3af standard, single port maximum access to 30W device, 4 prot total power does not exceed 70W (DC +48V/2A adapter), support over length cable (220 meters);
10	Peripheral Interface	2*USB2.0 interface (rear); support for the mouse, USB upgrade, import and export;
11	Front Panel	1* power, 1* record, 1* network indicator light;

12	Business Functions	Support preview/recording/forward/remote service, support alarm linkage, support Seetong client remote control software; support seetong cloud service;
13	Working Temperature	-10°C~+55°C
14	Working Humidity	10%~90%
15	Others	DC +48V/2A power input, host power consumption≤5W (No disk),size 255*210*42mm (W*D*H), weight 730g;