

NVR4.0 H.265 Series 8|16 channels

The most easy-to-use, popular and commercial 8|16 channel embedded NVR; specially design for store, small warehouse, office and family, access HD IPC, provide preview, recording, forward and so on functions. Support mobile phone monitoring, traversal service, achieve APP seconds connection for preview and remote recording playback, support various network modes:
 IPC----NVR---- Seetong Cloud----Seetong Client
 IPC-----NVR-----Seetong Client
 IPC----NVR---- Seetong Cloud----Seetong APP



H.265+, Stable, easy to use, perfect.

Orders	Specification	TS8108D4	TS8116D4
		1 Disk 8CH H.265+ NVR	1 Disk 8CH H.265+ NVR
1	System Structure	Embedded LINUX design, pure hardware decode, watchdog, hard disk storage, HDMI HD display, IP network video access.	
		Main processor Hi3536D;	
2	Video Input	HD IPC access, each channel support dual stream access, support auto search, add, recording, preview and without debugging;	
		Access bandwidth 48Mbps;	Access bandwidth 64Mbps;
3	Video Output	1channel HDMI output, 1 channel VGA output, homology with HDMI, support 1920×1080, 1440×900, 1366×768, 1280×1024, 1280×800, 1024×768 resolution output show;	
		Support Seetong client preview, APP preview and seconds connection	
		1/4/9 pictures real time preview;	1/2/4/6/8/9/10/16 pictures real time preview;
4	Video recording resolution	Support 720P/960P/1080P/3MP;	Support 720P/960P/1080P/3MP/4MP/5MP;
5	Video Capacity	Support H.265+/H.265/H.264 decoding;	
		NVR local recording playback support 1CH 3MP; Seetong client recording playback support 1 channels.	NVR local recording playback support 2CH 2MP, 1CH 5MP; Seetong client recording playback support 2 channels.
6	Audio	Standard G.711, support audio and video recording, support HDMI output channel preview and playback audio and video, Seetong client audio and video preview and playback;	
7	Storage	1*SATA hard disk interface, support 8TB capacity;	
		Support schedule record, motion detection linkage record;	
		Support external USB storage devices (such as ordinary U disk, mobile hard disk) backup;	
8	User	Local maximum support for 16 users;	
9	Network Interface	1*RJ45 Ethernet interface, support 10/100M self-adaption; support TCP/IP, IPv4, DHCP, NTP, RTSP, ONVIF, P2P, SMTP and so on protocols;	
10	Peripheral Interface	2*USB2.0 interface(rear); support for the mouse, USB upgrade, import and export;	
11	Front Panel	1* power, 1*record, 1*network indicator light;	
12	Business Functions	Support preview/recording/forward/remote service, support alarm linkage, support Seetong client remote control software; support seetong cloud service;	

13	Working Temperature	-10°C~+55°C	
14	Working Humidity	10%~90%	
15	Others	DC +12V/2A power input, hots power consumption≤3W (No disk), size 255*210*42mm (W*D*H), weight 620g;	DC +12V/2A power input, hots power consumption≤3W (No disk), size 255*210*42mm (W*D*H), weight 626g;
16	Optional	Support buzzer, audio output optional.	Support audio output optional.